

Schlauchbeutelanlage

Form Fill Seal Machine

NEU



BX Serie
BX Series

Schlauchbeutelanlage

Form- fill- and seal machine

Allgemein

- SPS Steuerung und Touch panel zur einfachen Bedienung
- Intelligente Temperaturregelung
- Schweißeinheit mit Servo
- Antrieb Servo Antrieb
- Folienabzug
- Doppeltransport möglich
- Sick Markenleser
- schneller Formatwechsel, kein Werkzeug benötigt

General

- PLC controller and touch screen interface for easy operation
- Intelligent temperature control system
- Sealing unit with servomotor
- Servo drive for film pulling system
- Double feed possible
- Sick eye mark sensor
- Quickly former change, not tools required

Modell <i>model</i>	BX-400	BX-500	BX-620	BX-800
Folienbreite <i>Film width</i>	Max. 400 mm	Max. 500 mm	Max. 620 mm	Max. 800 mm
Beutelbreite <i>Bag width</i>	60 – 190 mm	80 – 240 mm	110 – 300 mm	160 – 390 mm
Beutellänge <i>Bag length</i>	50 – 230 mm	50 – 300 mm	50 – 380 mm	100 – 480 mm
Folienmaterial <i>Film material</i>	Single Layer or Laminated	Single Layer or Laminated	Single Layer or Laminated	Single Layer or Laminated
Geschwindigkeit <i>Packing speed</i>	Max. 100 / min	Max. 100 / min	Max. 100 / min	Max. 100 / min
Luftverbrauch <i>Air request</i>	0.2 m ³ /min, 0,6 Mpa	0.2 m ³ /min, 0,6 Mpa	0.2 m ³ /min, 0,6 Mpa	0.2 m ³ /min, 0,6 Mpa
Spannung <i>electricity</i>	230V 50Hz 3,5 kW	230V 50Hz 4 kW	230V 50Hz 4.5 kW	230V 50Hz 5 kW
Größe <i>Dimension</i>	1.300 x 960 x 1.150 mm	1.550 x 1.160 x 1.480mm	1.600 x 1.260 x 1.680mm	1.680 x 1.400 x 1.850mm
Technische Änderungen ohne Vorankündigung vorbehalten <i>Subject to change without prior notice</i>				